

Features:

M-DRIVER-30-CV

LIGHTING DRIVER SOLUTIONS

Metro ELV Constant Voltage*, Class 2, Dimmable LED Drivers (30W, 24/12 V DC). Fireproof, Environmentally friendly PC cover. Short Circuit and overload protected. Integral wiring compartment.

* Constant Current Versions are available, not shown.

Output Power

AC Frequency

Power Factor

Efficiency

Lifetime

Length Width

Height

Operating Temp

Distributed by



Mormax Company, Inc. 8 Westchester Plaza Elmsford, NY 10523



914-699-0101 sales@mormax.com mormax.com

Input Voltage 100-120 VAC • FIREPROOF, ENVIRONMENTALLY
Output Voltage 24 V DC FRIENDLY PC COVER

30W

50-60 Hz

>.95 -30°C - 45°C

>85%

>50,000 hrs. @ Tc Max

4.21" (107.000mm)

1.61" (41.000mm)

0.87" (22.000mm)

• CLASS 2

• ETL LISTED

 SHORT CIRCUIT AND OVERLOAD PROTECTED

• INTEGRAL WIRING COMPARTMENT

• TRIAC, FORWARD & REVERSE PHASE DIMMING COMPATIBLE

• 120 VAC CORD & PLUG

• 20 AWG LOW VOLTAGE LEAD WIRE WITH BARREL JACK

M-DRIVER-30-CV





24 V DC WIRING COMPARTMENT



